

Data Sheet

We make sure



SCENICVIEW E22W-1 22 Inch LCD widescreen Display Preliminary

Issue October 2007

Pages 2

An attractive price doesn't mean that you have to compromise on style or performance. The SCENICVIEW E22W-1 widescreen display offers best performance for the office and multimedia. With its slim and stylish design, the SCENICVIEW E22W-1 fits perfectly into your office environment.

Highlights

- 22-inch widescreen display for a perfect viewing experience at high resolution
- Best performance to an affordable price
- Very easy and comfortable to use
 - Plug & Play
 - Auto-adjust
 - Easy-to-use OSD menu

Ergonomics

- Optimum flicker-free and distortion-free picture
- Excellent colour purity
- Well balanced brightness uniformity
- Excellent high contrast (800:1)
- Space saving design

Technical highlights

- 22" (55.9 cm) LCD widescreen display
- Excellent contrast **700:1**
- Brightness 300 cd/m²
- Fast response time (typ.) 5 ms
- Internal power supply

Reliability

- Low power consumption (EPA 'On Mode' 33W)
- Power management according to EPA
- Guaranteed quality and stability



Visible screen diagonal	22 inch (55.9 cm)
Resolutions	
Pixels	1680 x 1050
Pixels*	1280 x 768
* expanded	
Picture size	473.76 x 296.1 mm
Colours	16.7 million
Pixel Pitch	0.282 mm
Frequencies	
Horizontal	31 - 83 kHz
Vertical	56 - 75 Hz
Brightness (typical)	300 cd/m ²
Contrast (typical)	700:1
Viewing angle (typical)	
Horizontal	170°
Vertical	160°
Response time (typical)	5 ms
Plug and Play	VESA DDC2B
Setting options	
Brightness (Back light control)	
Contrast, Volume control	
Picture position (horizontal and vertical), H-size, Phase,	
Color temperature and individual color setting	
Auto-adjust (direct access key)	
Activate factory settings	
Menu language	
OSD Language	
English, German, Spanish, French, Italian, Russian, Polish, Dutch	
Base	
Tilt angle	-5°/ +20°
Audio characteristics	
Audio signal input	3.5mm stereo phone jack
Audio output	1 W (L) + 1 W (R)

Electrical values (internal power supply)

Power draw	
EPA 'Standby'	< 1 W
EPA 'On Mode'	33 W
Max.	< 55 W
Rated voltage	100 - 230 V
Frequency	50 - 60 Hz
Protection class	1

Temperatures/ dimensions/ weight

Ambient temperature (to IEC721):	
Working (recommended)	5°C to 35°C
Storage	-20°C to 60°C
Dimensions (H x W x D):	
(with stand)	418 x 514 x 219 mm
Weight (Monitor only)	5.4 kg

Reliability

MTBF (demonstrated)	60,000 h
Lifetime of LCD backlight	40,000 h
(brightness > 50 % of original brightness)	

Compliance with standards

Product safety	EN60950
Ergonomics	GS mark
	ISO13406-2
	(Pixel fault class II)
Radiation immunity and RFI suppression	CE certification according to EC Directive 89/336/EEC
	(EN55022/B, EN55024
	EN61000-3-2/-3);
	TCO'03

Video input	1 x D-SUB, 1 x DVI-D
--------------------	----------------------

Accessories

1 x Power cable (1.5 m)*	1 x wall socket (Euro-Schuko-Type CEE7)
Data cable (1.5 m)*	D-SUB (15-pin)
Audio cable (1.8 m)*	3.5mm stereo phone jack
* detachable on display	

Special features

Standardized mounting interface according VESA FPMPI (100 mm) Kensington Lock

Order code	S26361-K1200-V381
	EAN: 433364 3414597